



**MATERIALS:**

TUBE: Neoprene

COVER: Neoprene

REINFORCEMENT: Nylon Tire Cord

FLANGE: Zinc Plated Steel

QTY.	PART No.	SIZE (in.)	OAL (in.)	W/P (psi)			COMP. (in.)	ELONG. (in.)	LAT. (in.)	ANG. (°)	VAC. (in. Hg.)	WT. (lbs.)
				170°F.	200°F.	220°F.						
	SEMSD-200	2	7	225	190	150	1	3/4	1	30	16	10
	SEMSD-250	2-1/2	7	225	190	150	1	3/4	1	30	16	13
	SEMSD-300	3	7	225	190	150	1	3/4	1	30	16	14
	SEMSD-400	4	9	225	190	150	1-1/4	1	1-1/4	30	16	15
	SEMSD-500	5	9	225	190	150	1-1/4	1	1-1/4	30	16	24
	SEMSD-600	6	9	225	190	150	1-1/4	1	1-1/4	30	16	33
	SEMSD-800	8	13	225	190	150	1-1/2	1	1-3/8	30	16	48
	SEMSD-1000	10	13	225	190	150	1-1/2	1	1-3/8	30	16	65
	SEMSD-1200	12	13	225	190	150	1-1/2	1	1-3/8	30	16	76

CUSTOMER \_\_\_\_\_  
 PROJECT \_\_\_\_\_  
 ENGINEER \_\_\_\_\_  
 ARCHITECT \_\_\_\_\_  
 PRO./PO No. \_\_\_\_\_



**SOUTHEASTERN HOSE, INC.**  
 Bremen, GA 30110

**DOUBLE SPHERE RUBBER CONNECTOR  
 SUBMITTAL DATA**

DESCRIPTION: